

Building Department
 Village Of Mineola
 155 Washington Avenue
 Mineola, New York 11501

Phone 746-0750
 Fax 746-4065

Plumbing Permit Application

COPIES OR FAXES OF THIS APPLICATION ARE NOT ACCEPTED

Address of work: _____

Plumber Information

Company name: _____

Address: _____

Phone: _____

I understand all work must be performed by my employees under my direct supervision or by myself. I have read and understand the code, supplements and ordinances of the Village of Mineola. All work must conform to the New York State Building and Fire Prevention code.

Print Name: _____

Signature: _____

Notary Stamp

Boiler & Make

Size

Oil or Gas

Hot Water Heater & Make

Size

Oil or Gas

ALL NEW WORK REQUIRES A WATER TEST

(MUST BE COMPLETED)

Brief Description of Work:

Approved: _____ Date: _____

Permit No. _____ Fee: _____

Property Owner Information

Name: _____

Address: _____

Phone: _____

How is building to be occupied?

If residence, how many families or apartments?

I have reviewed the plumber's insurance and found them to be acceptable.

Print Name: _____

Signature: _____

Notary Stamp

(MUST BE COMPLETED)

Indicate Number	Base	1st	2nd	3rd
Fixtures	ment	floor	floor	floor
Water Closet				
Urinals				
Wash Sinks				
Bath Tubs				
Wash Tubs				
Sinks				
Dental Cuspidors				
Slop Sinks				
Drinking Fountains				
Stall Showers				
Gas Piping				
Hot Water Tanks				
Refrigerator				
Indirect Waste				
Other				

New York State Plumbing Code
Section 312 - Tests and Inspections

312.1.2 Required inspections. The holder of the permit shall be responsible for the scheduling of the following inspections:

1. Underground inspection shall be made after trenches or ditches are excavated and bedded, piping installed, and before any backfill is put in place.
2. Rough-in inspection shall be made of completed portions of all sanitary, storm, and water distribution piping, after the framing, fire blocking, fire stopping, draft stopping and bracing for that portion is in place, and prior to the installation of wall or ceiling membranes.
3. Final inspection shall be made after the building is complete, all plumbing fixtures are in place and properly connected, and the structure is ready for occupancy.

312.2 Drainage and vent water test. A water test shall be applied to the drainage system either in its entirety or in sections. If applied to the entire system, all openings in the piping shall be tightly closed, except the highest opening, and the system shall be filled with water to the point of overflow. If the system is tested in sections, each opening shall be tightly plugged except the highest openings of the section under test, and each section shall be filled with water, but no section shall be tested with less than a 10-foot head of water. The water shall be kept in the system or the portion under test for at least 15 minutes before inspection starts. The system shall then be tight at all points.

312.5 Water supply system test. Upon completion of a section of, or the entire water supply system, the system, or portion completed, shall be tested and proved tight under a water pressure not less than the working pressure of the system.

312.6 Gravity sewer test. Gravity sewer tests shall consist of plugging the end of the building sewer at the point of connection with the public sewer, filling the building sewer with water, testing with not less than a 10-foot head of water and maintaining such pressure for 15 minutes.